

VV-K 0,6/1 kV

Iberflex 0,6/1 kV

APPLICATIONS

For fix and underground installations, industrial connections, electric valves, machinery and internal distribution installations.

TECHNICAL SPECIFICATIONS

- 1.- Flexible electrolytic **copper conductive** type 5 according to UNE-EN 60228
- 2.- **PVC insulation type A** according to UNE 21123 – IEC 60502-1
- 3.- **PVC sheath** type ST-1 according to 21123 – IEC 60502-1

Nominal tension: 0.6/1 kV
 Maximum temperature of service: 70 °C
 Dielectric rigidity: 3.500 V

| Section (mm ²) | Resistance at 20°C (Ω/Km) | Outer diameter (mm) |
|-------------------------------|---------------------------------|------------------------|
| 2x1,5 | 13,30 | 9,05 |
| 2x2,5 | 7,98 | 10,00 |
| 2x4 | 4,95 | 11,50 |
| 2x6 | 3,30 | 12,85 |
| 3x1,5 | 13,30 | 9,55 |
| 3x2,5 | 7,98 | 10,60 |
| 3x4 | 4,95 | 12,25 |
| 3x6 | 3,30 | 13,65 |
| 4x1,5 | 13,30 | 10,35 |
| 4x4 | 4,95 | 13,35 |
| 5x1,5 | 13,30 | 11,25 |
| 5x2,5 | 7,98 | 12,60 |
| 6x1,5 | 13,30 | 12,20 |

REBT 2002 REGULATION

ITC-BT 09 Usage in exterior lightning installations and earth installations.

ITC-BT 20 Usage in interior or receiving installations.

The information contained on this page are purely informational and doesn't constitute any contractual commitment by Ibercable SL. The company reserves the right to change technical specifications without prior notice.

